



CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y21	2	NC
3	Y20	3	NC
4	Y19	4	NC
5	Y18	5	NC
6	Y17	6	NC
7	Y16	7	NC
8	Y15	8	NC
9	Y14	9	NC
10	Y13	10	Dummy
11	Y12	11	X28
12	Y11	12	X27
13	Y10	13	X26
14	Y09	14	X25
15	Y08	15	X24
16	Y07	16	X23
17	Y06	17	X22
18	Y05	18	X21
19	Y04	19	X20
20	Y03	20	X19
21	Y02	21	X18
22	Y01	22	X17
23	Y00	23	X16
24	Dummy	24	X15
25	NC	25	X14
26	NC	26	X13
		27	X12
		28	X11
		29	X10
		30	X09
		31	X08
		32	X07
		33	X06
		34	X05
		35	X04
		36	X03
		37	X02
		38	X01
		39	X00
		40	Dummy

REMARKS		
FPC PATTERN PITCH	Cu	0.5mm
FPC PATTERN WIDTH	-	0.2-0.3mm
CIRCUIT PATTERN WIDTH	Ag	0.075mm
O TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1	TOP ITO GLASS	t=1.1mm
2	BOTTOM ITO GLASS	t=1.1mm
3	FPC	POLYIMIDE 12.5μm Electrolytic copper foil GLDMS
4	REINFORCEMENT FILM	POLYIMIDE 25μm
5	STIFFENER	POLYIMIDE 225μm
6	ADHESIVE SHEET	150μm
7	PROTECTION TAPE	POLYESTER 25μm

TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

PART No.	DATE
DUS-A084A060A	Jan/28/2021
TYPE	DMC Co., Ltd.
Projected Capacitive	
DIMENSIONAL DRAWING	