


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y19	2	NC
3	Y18	3	NC
4	Y17	4	NC
5	Y16	5	Dummy
6	Y15	6	X33
7	Y14	7	X32
8	Y13	8	X31
9	Y12	9	X30
10	Y11	10	X29
11	Y10	11	X28
12	Y09	12	X27
13	Y08	13	X26
14	Y07	14	X25
15	Y06	15	X24
16	Y05	16	X23
17	Y04	17	X22
18	Y03	18	X21
19	Y02	19	X20
20	Y01	20	X19
21	Y00	21	X18
22	Dummy	22	X17
23	NC	23	X16
24	NC	24	X15
25	NC	25	X14
26	NC	26	X13
		27	X12
		28	X11
		29	X10
		30	X09
		31	X08
		32	X07
		33	X06
		34	X05
		35	X04
		36	X03
		37	X02
		38	X01
		39	X00
		40	Dummy

REMARKS			
FPC PATTERN PITCH			0.5mm
FPC PATTERN WIDTH	Cu		0.2-0.3mm
	-		mm
CIRCUIT PATTERN WIDTH	Ag		0.075mm
	-		mm
O TOLERANCE=±0.3mm			

ITEM	MATERIAL	REMARKS
1	TOP ITO GLASS	t=1.1mm
2	BOTTOM ITO GLASS	t=1.1mm
3	FPC	POLYIMIDE 12.5μm Electrolytic copper foil GILDING
4	REINFORCEMENT FILM	POLYIMIDE 25μm
5	STIFFENER	POLYIMIDE 225μm
6	ADHESIVE SHEET	150μm
7	PROTECTION TAPE	POLYESTER 25μm



TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

PART No.	DATE
DUS-A090WA060A/wv	Jan/28/2021
TYPE	DMC Co., Ltd.
Projected Capacitive DIMENSIONAL DRAWING	