

CN-1 PinOut	
1	Dummy
2	Y22
3	Y20
4	Y19
5	Y18
6	Y17
7	Y16
8	Y15
9	Y14
10	Y13
11	Y12
12	Y11
13	Y10
14	Y09
15	Y08
16	Y07
17	Y06
18	Y05
19	Y04
20	Y03
21	Y02
22	Y01
23	Y00
24	Dummy
25	Dummy
26	NC


CN-2 PinOut	
1	NC
2	Dummy
3	X36
4	X35
5	X34
6	X33
7	X32
8	X31
9	X30
10	X29
11	X28
12	X27
13	X26
14	X25
15	X24
16	X23
17	X22
18	X21
19	X20
20	X19
21	X18
22	X17
23	X16
24	X15
25	X14
26	X13
27	X12
28	X11
29	X10
30	X09
31	X08
32	X07
33	X06
34	X05
35	X04
36	X03
37	X02
38	X01
39	X00
40	Dummy

Reference point

CN-1 Contact surface far side 26 1 40  
 CN-2 Contact surface far side 1

REMARKS		
FPC PATTERN PITCH		0.5mm
FPC PATTERN WIDTH	Cu	0.2-0.3mm
		mm
CIRCUIT PATTERN WIDTH	Ag	0.1mm
		mm
O TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1 TOP ITO GLASS	t=1.1mm	
2 BOTTOM ITO GLASS	t=1.1mm	
3 FPC	POLYIMIDE 12.5μm	Electrolytic copper foil 0.03mm
4 REINFORCEMENT FILM	POLYIMIDE 25μm	
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	150μm	
7 PROTECTION TAPE	POLYESTER 25μm	



TOLERANCE=±0.3mm  
 EXCEPT WHERE INDICATED  
 UNIT=mm

PART No.		DATE	
DUS-A101WB060A		Feb/24/2023	
TYPE		DMC Co., Ltd.	
Projected Capacitive			
DIMENSIONAL DRAWING			