


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y15	2	NC
3	Y14	3	NC
4	Y13	4	NC
5	Y12	5	NC
6	Y11	6	NC
7	Y10	7	NC
8	Y09	8	NC
9	Y08	9	NC
10	Y07	10	NC
11	Y06	11	NC
12	Y05	12	NC
13	Y04	13	Dummy
14	Y03	14	X25
15	Y02	15	X24
16	Y01	16	X23
17	Y00	17	X22
18	Dummy	18	X21
19	NC	19	X20
20	NC	20	X19
21	NC	21	X18
22	NC	22	X17
23	NC	23	X16
24	NC	24	X15
25	NC	25	X14
26	NC	26	X13
		27	X12
		28	X11
		29	X10
		30	X09
		31	X08
		32	X07
		33	X06
		34	X05
		35	X04
		36	X03
		37	X02
		38	X01
		39	X00
		40	Dummy

REMARKS		
FPC PATTERN PITCH		0.5mm
FPC PATTERN WIDTH	Cu	0.2-0.3mm
	-	mm
CIRCUIT PATTERN WIDTH	Ag	0.1mm
	-	mm
O TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1 TOP ITO FILM	t=0.1mm	
2 BOTTOM ITO FILM	t=0.1mm	
3 FPC	POLYIMIDE 12.5μm	Electrolytic copper foil GOLDING
4 REINFORCEMENT FILM	POLYIMIDE 25μm	
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	OCA 50μm	
7 ADHESIVE SHEET A	OCA 50μm	
8 COVER GLASS	t=1.8mm	Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

PART No.	DATE
DUS-F070WA060A2A	Jan/25/2021
TYPE	DMC Co., Ltd.
Projected Capacitive	
DIMENSIONAL DRAWING	

