


| CN-1 PinOut | | CN-2 PinOut | |
|-------------|-------|-------------|-------|
| 1 | Dummy | 1 | NC |
| 2 | Y22 | 2 | Dummy |
| 3 | Y21 | 3 | X36 |
| 4 | Y20 | 4 | X35 |
| 5 | Y19 | 5 | X34 |
| 6 | Y18 | 6 | X33 |
| 7 | Y17 | 7 | X32 |
| 8 | Y16 | 8 | X31 |
| 9 | Y15 | 9 | X30 |
| 10 | Y14 | 10 | X29 |
| 11 | Y13 | 11 | X28 |
| 12 | Y12 | 12 | X27 |
| 13 | Y11 | 13 | X26 |
| 14 | Y10 | 14 | X25 |
| 15 | Y09 | 15 | X24 |
| 16 | Y08 | 16 | X23 |
| 17 | Y07 | 17 | X22 |
| 18 | Y06 | 18 | X21 |
| 19 | Y05 | 19 | X20 |
| 20 | Y04 | 20 | X19 |
| 21 | Y03 | 21 | X18 |
| 22 | Y02 | 22 | X17 |
| 23 | Y01 | 23 | X16 |
| 24 | Y00 | 24 | X15 |
| 25 | Dummy | 25 | X14 |
| 26 | NC | 26 | X13 |
| | | 27 | X12 |
| | | 28 | X11 |
| | | 29 | X10 |
| | | 30 | X09 |
| | | 31 | X08 |
| | | 32 | X07 |
| | | 33 | X06 |
| | | 34 | X05 |
| | | 35 | X04 |
| | | 36 | X03 |
| | | 37 | X02 |
| | | 38 | X01 |
| | | 39 | X00 |
| | | 40 | Dummy |

| REMARKS | | |
|-----------------------|----|-----------|
| FPC PATTERN PITCH | | 0.5mm |
| FPC PATTERN WIDTH | Cu | 0.2-0.3mm |
| | - | mm |
| CIRCUIT PATTERN WIDTH | Ag | 0.1mm |
| | - | mm |
| O TOLERANCE=±0.3mm | | |

| ITEM | MATERIAL | REMARKS |
|----------------------|------------------|--|
| 1 TOP ITO FILM | t=0.1mm | |
| 2 BOTTOM ITO FILM | t=0.1mm | |
| 3 FPC | POLYIMIDE 12.5μm | Electromagnetic copper foil blocking |
| 4 REINFORCEMENT FILM | POLYIMIDE 25μm | |
| 5 STIFFENER | POLYIMIDE 225μm | |
| 6 ADHESIVE SHEET | OCA 50μm | |
| 7 ADHESIVE SHEET A | OCA | |
| 8 COVER GLASS | t=1.8mm | Clear/Chemical strengthening Black printing |



TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

| | |
|----------------------|---------------|
| PART No. | DATE |
| DUS-F101WA060A2A | Jan/25/2021 |
| TYPE | DMC Co., Ltd. |
| Projected Capacitive | |
| DIMENSIONAL DRAWING | |