


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y35	2	NC
3	Y34	3	NC
4	Y33	4	NC
5	Y32	5	NC
6	Y31	6	Dummy
7	Y30	7	X4.6
8	Y29	8	X4.5
9	Y28	9	X4.4
10	Y27	10	X4.3
11	Y26	11	X4.2
12	Y25	12	X4.1
13	Y24	13	X4.0
14	Y23	14	X3.9
15	Y22	15	X3.8
16	Y21	16	X3.7
17	Y20	17	X3.6
18	Y19	18	X3.5
19	Y18	19	X3.4
20	Y17	20	X3.3
21	Y16	21	X3.2
22	Y15	22	X3.1
23	Y14	23	X3.0
24	Y13	24	X2.9
25	Y12	25	X2.8
26	Y11	26	X2.7
27	Y10	27	X2.6
28	Y09	28	X2.5
29	Y08	29	X2.4
30	Y07	30	X2.3
31	Y06	31	X2.2
32	Y05	32	X2.1
33	Y04	33	X2.0
34	Y03	34	X1.9
35	Y02	35	X1.8
36	Y01	36	X1.7
37	Y00	37	X1.6
38	Dummy	38	X1.5
39	NC	39	X1.4
40	NC	40	X1.3
		41	X1.2
		42	X1.1
		43	X1.0
		44	X0.9
		45	X0.8
		46	X0.7
		47	X0.6
		48	X0.5
		49	X0.4
		50	X0.3
		51	X0.2
		52	X0.1
		53	X0.0
		54	Dummy
		55	NC

REMARKS		
FPC PATTERN PITCH	Cu	0.5mm
FPC PATTERN WIDTH	Cu	0.2-0.3mm
	Ag	mm
CIRCUIT PATTERN WIDTH	Ag	0.1mm
		mm
TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1	TOP ITO FILM	t=0.1mm
2	BOTTOM ITO FILM	t=0.1mm
3	FPC	POLYIMIDE 12.5μm Electroplated copper foil (90%)
4	REINFORCEMENT FILM	POLYIMIDE 25μm
5	STIFFENER	POLYIMIDE 225μm
6	ADHESIVE SHEET	OCA 50μm
7	ADHESIVE SHEET A	OCA 100μm
8	COVER GLASS	t=1.8mm Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm  
EXCEPT WHERE INDICATED  
UNIT=mm

PART No.	DATE	
DUS-F150A060B2A	Jan/25/2021	
TYPE	DMC Co., Ltd.	
Projected Capacitive DIMENSIONAL DRAWING		