


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y15	2	NC
3	Y14	3	NC
4	Y13	4	NC
5	Y12	5	NC
6	Y11	6	NC
7	Y10	7	NC
8	Y09	8	NC
9	Y08	9	NC
10	Y07	10	NC
11	Y06	11	NC
12	Y05	12	NC
13	Y04	13	Dummy
14	Y03	14	X25
15	Y02	15	X24
16	Y01	16	X23
17	Y00	17	X22
18	Dummy	18	X21
19	NC	19	X20
20	NC	20	X19
21	NC	21	X18
22	NC	22	X17
23	NC	23	X16
24	NC	24	X15
25	NC	25	X14
26	NC	26	X13
		27	X12
		28	X11
		29	X10
		30	X09
		31	X08
		32	X07
		33	X06
		34	X05
		35	X04
		36	X03
		37	X02
		38	X01
		39	X00
		40	Dummy

REMARKS	
FPC PATTERN PITCH	0.5mm
FPC PATTERN WIDTH	Cu 0.2-0.3mm
	- mm
CIRCUIT PATTERN WIDTH	Ag 0.1-0.2mm
	- mm
O TOLERANCE=±0.3mm	

ITEM	MATERIAL	REMARKS
1	TOP ITO GLASS t=1.1mm	
2	BOTTOM ITO GLASS t=1.1mm	
3	FPC POLYIMIDE 12.5μm	Electrolytic copper foil GILDING
4	REINFORCEMENT FILM POLYIMIDE 25μm	
5	STIFFENER POLYIMIDE 225μm	
6	ADHESIVE SHEET 150μm	
7	PROTECTION TAPE POLYESTER 25μm	
8	COVER GLASS t=1.1mm	Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm  
EXCEPT WHERE INDICATED  
UNIT=mm

PART No.	DATE
DUS-LA070WB060A1A	Aug/5/2022
TYPE	DMC Co., Ltd.
Projected Capacitive DIMENSIONAL DRAWING	