


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y26	2	NC
3	Y25	3	NC
4	Y24	4	NC
5	Y23	5	NC
6	Y22	6	NC
7	Y21	7	NC
8	Y20	8	NC
9	Y19	9	NC
10	Y18	10	NC
11	Y17	11	NC
12	Y16	12	NC
13	Y15	13	NC
14	Y14	14	NC
15	Y13	15	NC
16	Y12	16	NC
17	Y11	17	Dummy
18	Y10	18	X35
19	Y09	19	X34
20	Y08	20	X33
21	Y07	21	X32
22	Y06	22	X31
23	Y05	23	X30
24	Y04	24	X29
25	Y03	25	X28
26	Y02	26	X27
27	Y01	27	X26
28	Y00	28	X25
29	Dummy	29	X24
30	NC	30	X23
31	NC	31	X22
32	NC	32	X21
33	NC	33	X20
34	NC	34	X19
35	NC	35	X18
36	NC	36	X17
37	NC	37	X16
38	NC	38	X15
39	NC	39	X14
40	NC	40	X13
41	NC	41	X12
42	NC	42	X11
43	NC	43	X10
44	NC	44	X09
45	NC	45	X08
46	NC	46	X07
47	NC	47	X06
48	NC	48	X05
49	NC	49	X04
50	NC	50	X03
51	NC	51	X02
52	NC	52	X01
53	NC	53	X00
54	Dummy	54	Dummy
55	NC	55	NC

REMARKS		
FPC PATTERN PITCH		0.5mm
FPC PATTERN WIDTH	Cu	0.2-0.3mm
	-	mm
CIRCUIT PATTERN WIDTH	Ag	0.1-0.2mm
	-	mm
O TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1 TOP ITO GLASS	t=1.1mm	
2 BOTTOM ITO GLASS	t=1.1mm	
3 FPC	POLYIMIDE 12.5μm	Electrolytic copper foil
4 REINFORCEMENT FILM	POLYIMIDE 25μm	GLONG
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	150μm	
7 PROTECTION TAPE	POLYESTER 25μm	
8 COVER GLASS	t=1.8mm	Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

PART No.	DATE	
DUS-LA104B060B2A	Jan/21/2021	
TYPE	DMC Co., Ltd.	
Projected Capacitive		
DIMENSIONAL DRAWING		