


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y27	2	NC
3	Y26	3	NC
4	Y25	4	NC
5	Y24	5	NC
6	Y23	6	NC
7	Y22	7	NC
8	Y21	8	NC
9	Y20	9	Dummy
10	Y19	10	X43
11	Y18	11	X42
12	Y17	12	X41
13	Y16	13	X40
14	Y15	14	X39
15	Y14	15	X38
16	Y13	16	X37
17	Y12	17	X36
18	Y11	18	X35
19	Y10	19	X34
20	Y09	20	X33
21	Y08	21	X32
22	Y07	22	X31
23	Y06	23	X30
24	Y05	24	X29
25	Y04	25	X28
26	Y03	26	X27
27	Y02	27	X26
28	Y01	28	X25
29	Y00	29	X24
30	Dummy	30	X23
31	NC	31	X22
32	NC	32	X21
33	NC	33	X20
34	NC	34	X19
35	NC	35	X18
36	NC	36	X17
37	NC	37	X16
38	NC	38	X15
39	NC	39	X14
40	NC	40	X13
41	NC	41	X12
42	NC	42	X11
43	NC	43	X10
44	NC	44	X09
45	NC	45	X08
46	NC	46	X07
47	NC	47	X06
48	NC	48	X05
49	NC	49	X04
50	NC	50	X03
51	NC	51	X02
52	NC	52	X01
53	NC	53	X00
54	Dummy	54	Dummy
55	NC	55	NC

REMARKS	
FPC PATTERN PITCH	0.5mm
FPC PATTERN WIDTH	Cu 0.2-0.3mm
CIRCUIT PATTERN WIDTH	Ag mm
	0.075mm
O TOLERANCE=±0.3mm	

ITEM	MATERIAL	REMARKS
1 TOP ITO GLASS	t=1.1mm	
2 BOTTOM ITO GLASS	t=1.1mm	
3 FPC	POLYIMIDE 12.5μm	Electrolytic copper foil GILDING
4 REINFORCEMENT FILM	POLYIMIDE 25μm	
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	150μm	
7 PROTECTION TAPE	POLYESTER 25μm	
8 COVER GLASS	t=1.1mm	Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm  
EXCEPT WHERE INDICATED  
UNIT=mm

PART No.	DATE
DUS-LA121WA060B1A	Jan/21/2021
TYPE	DMC Co., Ltd.
Projected Capacitive DIMENSIONAL DRAWING	