


CNT PinOut		CN2 PinOut	
1	Dummy	1	NC
2	Y38	2	NC
3	Y37	3	NC
4	Y36	4	NC
5	Y35	5	NC
6	Y34	6	NC
7	Y33	7	NC
8	Y32	8	NC
9	Y31	9	NC
10	Y30	10	Dummy
11	Y29	11	X68
12	Y28	12	X67
13	Y27	13	X66
14	Y26	14	X65
15	Y25	15	X64
16	Y24	16	X63
17	Y23	17	X62
18	Y22	18	X61
19	Y21	19	X60
20	Y20	20	X59
21	Y19	21	X58
22	Y18	22	X57
23	Y17	23	X56
24	Y16	24	X55
25	Y15	25	X54
26	Y14	26	X53
27	Y13	27	X52
28	Y12	28	X51
29	Y11	29	X50
30	Y10	30	X49
31	Y09	31	X48
32	Y08	32	X47
33	Y07	33	X46
34	Y06	34	X45
35	Y05	35	X44
36	Y04	36	X43
37	Y03	37	X42
38	Y02	38	X41
39	Y01	39	X40
40	Y00	40	X39
41	Dummy	41	X38
42	NC	42	X37
43	NC	43	X36
44	NC	44	X35
45	NC	45	X34
46	NC	46	X33
47	NC	47	X32
48	NC	48	X31
49	NC	49	X30
50	NC	50	X29
51	NC	51	X28
52	NC	52	X27
53	NC	53	X26
54	NC	54	X25
55	NC	55	X24
		56	X23
		57	X22
		58	X21
		59	X20
		60	X19
		61	X18
		62	X17
		63	X16
		64	X15
		65	X14
		66	X13
		67	X12
		68	X11
		69	X10
		70	X09
		71	X08
		72	X07
		73	X06
		74	X05
		75	X04
		76	X03
		77	X02
		78	X01
		79	X00
		80	Dummy

REMARKS	
FPC PATTERN PITCH	0.5mm
FPC PATTERN WIDTH	Cu 0.2-0.3mm
	Ag mm
CIRCUIT PATTERN WIDTH	Ag 0.1-0.2mm
	mm
○ TOLERANCE=±0.3mm	

ITEM	MATERIAL	REMARKS
1 TOP ITO GLASS	t=1.1mm	
2 BOTTOM ITO GLASS	t=1.1mm	
3 FPC	POLYIMIDE 12.5μm	Electric cover film
4 REINFORCEMENT FILM	POLYIMIDE 25μm	
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	POLYIMIDE 150μm	
7 PROTECTION TAPE	POLYESTER 25μm	
8 COVER GLASS	t=1.8mm	Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm
Edges and corners of ITO glass may be chamfered
without affecting product specification.

PART No.		DATE	
DUS-LA185WB060A2A		Aug/5/2022	
TYPE		DMC Co., Ltd.	
Projected Capacitive			
DIMENSIONAL DRAWING			