


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y21	2	NC
3	Y20	3	NC
4	Y19	4	NC
5	Y18	5	NC
6	Y17	6	NC
7	Y16	7	NC
8	Y15	8	NC
9	Y14	9	NC
10	Y13	10	Dummy
11	Y12	11	X28
12	Y11	12	X27
13	Y10	13	X26
14	Y09	14	X25
15	Y08	15	X24
16	Y07	16	X23
17	Y06	17	X22
18	Y05	18	X21
19	Y04	19	X20
20	Y03	20	X19
21	Y02	21	X18
22	Y01	22	X17
23	Y00	23	X16
24	Dummy	24	X15
25	NC	25	X14
26	NC	26	X13
		27	X12
		28	X11
		29	X10
		30	X09
		31	X08
		32	X07
		33	X06
		34	X05
		35	X04
		36	X03
		37	X02
		38	X01
		39	X00
		40	Dummy



REMARKS		
FPC PATTERN PITCH	Cu	0.5mm
FPC PATTERN WIDTH	-	0.2-0.3mm
CIRCUIT PATTERN WIDTH	Ag	mm
	-	0.03mm
○ELECTRODE PITCH: X=6.47mm, Y=6.33mm		
○TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1	TOP ITO GLASS	t=1.1mm
2	BOTTOM ITO GLASS	t=1.1mm
3	FPC	POLYIMIDE 12.5µm CONTACT-GILDING
4	REINFORCEMENT FILM	POLYIMIDE 25µm
5	STIFFENER	POLYIMIDE 225µm
6	ADHESIVE SHEET	150µm
7	PROTECTION TAPE	POLYESTER 25µm

§ Edges and corners of ITO glass may be chamfered without affecting product specification.

PART No.	DATE	SCALE
DUS-N084B060C	Jul/16/25	NTS
TYPE		UNIT
STANDARD TOUCHSCREEN		mm
DIMENSIONAL DRAWING	DMC Co., Ltd.	⊕

