


CN1 PinOut		CN2 PinOut	
1	Dummy	1	Dummy
2	Y43	2	X77
3	Y42	3	X76
4	Y41	4	X75
5	Y40	5	X74
6	Y39	6	X73
7	Y38	7	X72
8	Y37	8	X71
9	Y36	9	X70
10	Y35	10	X69
11	Y34	11	X68
12	Y33	12	X67
13	Y32	13	X66
14	Y31	14	X65
15	Y30	15	X64
16	Y29	16	X63
17	Y28	17	X62
18	Y27	18	X61
19	Y26	19	X60
20	Y25	20	X59
21	Y24	21	X58
22	Y23	22	X57
23	Y22	23	X56
24	Y21	24	X55
25	Y20	25	X54
26	Y19	26	X53
27	Y18	27	X52
28	Y17	28	X51
29	Y16	29	X50
30	Y15	30	X49
31	Y14	31	X48
32	Y13	32	X47
33	Y12	33	X46
34	Y11	34	X45
35	Y10	35	X44
36	Y09	36	X43
37	Y08	37	X42
38	Y07	38	X41
39	Y06	39	X40
40	Y05	40	X39
41	Y04	41	X38
42	Y03	42	X37
43	Y02	43	X36
44	Y01	44	X35
45	Y00	45	X34
46	Dummy	46	X33
47	NC	47	X32
48	NC	48	X31
49	NC	49	X30
50	NC	50	X29
51	NC	51	X28
52	NC	52	X27
53	NC	53	X26
54	NC	54	X25
55	NC	55	X24
		56	X23
		57	X22
		58	X21
		59	X20
		60	X19
		61	X18
		62	X17
		63	X16
		64	X15
		65	X14
		66	X13
		67	X12
		68	X11
		69	X10
		70	X09
		71	X08
		72	X07
		73	X06
		74	X05
		75	X04
		76	X03
		77	X02
		78	X01
		79	X00
		80	Dummy



REMARKS	
FPC PATTERN PITCH	0.5mm
FPC PATTERN WIDTH	Cu 0.2-0.3mm
	mm
CIRCUIT PATTERN WIDTH	Ag 0.03mm
	mm
TOLERANCE±0.3mm	

ITEM	MATERIAL	REMARKS
1	TOP ITO GLASS	t=1.1mm
2	BOTTOM ITO GLASS	t=1.1mm
3	FPC	POLYIMIDE 12.5μm
4	REINFORCEMENT FILM	POLYIMIDE 25μm
5	STIFFENER	POLYIMIDE 225μm
6	ADHESIVE SHEET	150μm
7	PROTECTION TAPE	POLYESTER 25μm

PART No.	DATE
DUS-N215WA060A	Jan/31/23
TYPE	
Projected Capacitive	
DIMENSIONAL DRAWING	DMC Co., Ltd.

TOLERANCE±0.3mm
EXCEPT WHERE INDICATED
UNIT:mm
Edges and corners of ITO glass may be chamfered without affecting product specification.

