



CN-1 PinOut		CN-2 PinOut	
1	NC	48	NC
2	NC	49	NC
3	NC	50	NC
4	ESD(R)	51	NC
5	NC	52	NC
6	NC	53	NC
7	NC	54	NC
8	GR	55	GR
9	RX30	56	TX17
10	RX29	57	TX16
11	RX28	58	TX15
12	RX27	59	TX14
13	RX26	60	TX13
14	RX25	61	TX12
15	RX24	62	TX11
16	RX23	63	TX10
17	RX22	64	TX09
18	RX21	65	TX08
19	RX20	66	TX07
20	RX19	67	TX06
21	RX18	68	TX05
22	RX17	69	TX04
23	RX16	70	TX03
24	RX15	71	TX02
25	RX14	72	TX01
26	RX13	73	TX00
27	RX12	74	NC
28	RX11	75	NC
29	RX10	76	NC
30	RX09	77	NC
31	RX08	78	NC
32	RX07	79	NC
33	RX06	80	GR
34	RX05	81	NC
35	RX04	82	NC
36	RX03	83	NC
37	RX02	84	ESD(L)
38	RX01	85	NC
39	RX00	86	NC
40	GR	87	NC
41	NC		
42	NC		
43	NC		
44	NC		
45	NC		
46	NC		
47	NC		

【 CN-3 PinOut 】

PIN No.	PIN Name	PIN No.	PIN Name
1	NC	6	I2C_SCL
2	NC	7	I2C_SDA
3	NC	8	I2C_INT
4	GND	9	RSTN
5	I2C_VDD	10	GND

REMARKS
 ORED: TX CIRCUIT, GREEN: RX CIRCUIT.
 OPURPLE: TX CIRCUIT, LIGHT BLUE: RX CIRCUIT.
 O TOLERANCE=±0.3mm

ITEM	MATERIAL	REMARKS
1 ITO GLASS	t=1.1mm	SITO
2 ADHESIVE SHEET	250μm	
3 Cover Glass	t=1.1mm	Clear/Chemical strengthening
4 PROTECTION TAPE	POLYESTER 25μm	
5 CoF	Polyimide with stiffener (SUS304) CoF: DUSF131	

PART No.	DATE	SCALE
DUS-S101WAF131	Nov/29/23	NTS
TYPE		UNIT
STANDARD TOUCHSCREEN		mm
DIMENSIONAL DRAWING	DMC Co., Ltd.	