



CN-1 PinOut		CN-2 PinOut	
1	NC	48	NC
2	NC	49	NC
3	NC	50	NC
4	ESD(R)	51	NC
5	NC	52	NC
6	NC	53	NC
7	NC	54	NC
8	GR	55	GR
9	RX30	56	TX19
10	RX29	57	TX18
11	RX28	58	TX17
12	RX27	59	TX16
13	RX26	60	TX15
14	RX25	61	TX14
15	RX24	62	TX13
16	RX23	63	TX12
17	RX22	64	TX11
18	RX21	65	TX10
19	RX20	66	TX09
20	RX19	67	TX08
21	RX18	68	TX07
22	RX17	69	TX06
23	RX16	70	TX05
24	RX15	71	TX04
25	RX14	72	TX03
26	RX13	73	TX02
27	RX12	74	TX01
28	RX11	75	TX00
29	RX10	76	NC
30	RX09	77	NC
31	RX08	78	NC
32	RX07	79	NC
33	RX06	80	GR
34	RX05	81	NC
35	RX04	82	NC
36	RX03	83	NC
37	RX02	84	ESD(L)
38	RX01	85	NC
39	RX00	86	NC
40	GR	87	NC
41	NC		
42	NC		
43	NC		
44	NC		
45	NC		
46	NC		
47	NC		

【 CN-3 PinOut 】

PIN No.	PIN Name	PIN No.	PIN Name
1	NC	6	I2C_SCL
2	NC	7	I2C_SDA
3	NC	8	I2C_INT
4	GND	9	RSTN
5	I2C_VDD	10	GND

REMARKS
 ORED: TX CIRCUIT, GREEN: RX CIRCUIT.
 OPURPLE: TX CIRCUIT, LIGHT BLUE: RX CIRCUIT.
 O TOLERANCE=±0.3mm

ITEM	MATERIAL	REMARKS
1 ITO GLASS	t=1.1mm	SITO
2 ADHESIVE SHEET	250μm	
3 Cover Glass	t=1.1mm	Clear/Chemical strengthening
4 PROTECTION TAPE	POLYESTER 25μm	
5 CoF	Polyimide with stiffener (SUS304) CoF: DUSF131	

PART No.	DATE	SCALE
DUS-S101WAF131/X2	Nov/29/23	NTS
TYPE		UNIT
STANDARD TOUCHSCREEN		mm
DIMENSIONAL DRAWING	DMC Co., Ltd.	