



| CN1 PinOut | | CN2 PinOut | |
|------------|-------|------------|-------|
| 1 | Dummy | 1 | NC |
| 2 | Y38 | 2 | NC |
| 3 | Y37 | 3 | NC |
| 4 | Y36 | 4 | NC |
| 5 | Y35 | 5 | NC |
| 6 | Y34 | 6 | NC |
| 7 | Y33 | 7 | NC |
| 8 | Y32 | 8 | NC |
| 9 | Y31 | 9 | NC |
| 10 | Y30 | 10 | Dummy |
| 11 | Y29 | 11 | X68 |
| 12 | Y28 | 12 | X67 |
| 13 | Y27 | 13 | X66 |
| 14 | Y26 | 14 | X65 |
| 15 | Y25 | 15 | X64 |
| 16 | Y24 | 16 | X63 |
| 17 | Y23 | 17 | X62 |
| 18 | Y22 | 18 | X61 |
| 19 | Y21 | 19 | X60 |
| 20 | Y20 | 20 | X59 |
| 21 | Y19 | 21 | X58 |
| 22 | Y18 | 22 | X57 |
| 23 | Y17 | 23 | X56 |
| 24 | Y16 | 24 | X55 |
| 25 | Y15 | 25 | X54 |
| 26 | Y14 | 26 | X53 |
| 27 | Y13 | 27 | X52 |
| 28 | Y12 | 28 | X51 |
| 29 | Y11 | 29 | X50 |
| 30 | Y10 | 30 | X49 |
| 31 | Y09 | 31 | X48 |
| 32 | Y08 | 32 | X47 |
| 33 | Y07 | 33 | X46 |
| 34 | Y06 | 34 | X45 |
| 35 | Y05 | 35 | X44 |
| 36 | Y04 | 36 | X43 |
| 37 | Y03 | 37 | X42 |
| 38 | Y02 | 38 | X41 |
| 39 | Y01 | 39 | X40 |
| 40 | Y00 | 40 | X39 |
| 41 | Dummy | 41 | X38 |
| 42 | NC | 42 | X37 |
| 43 | NC | 43 | X36 |
| 44 | NC | 44 | X35 |
| 45 | NC | 45 | X34 |
| 46 | NC | 46 | X33 |
| 47 | NC | 47 | X32 |
| 48 | NC | 48 | X31 |
| 49 | NC | 49 | X30 |
| 50 | NC | 50 | X29 |
| 51 | NC | 51 | X28 |
| 52 | NC | 52 | X27 |
| 53 | NC | 53 | X26 |
| 54 | NC | 54 | X25 |
| 55 | NC | 55 | X24 |
| 56 | | 56 | X23 |
| 57 | | 57 | X22 |
| 58 | | 58 | X21 |
| 59 | | 59 | X20 |
| 60 | | 60 | X19 |
| 61 | | 61 | X18 |
| 62 | | 62 | X17 |
| 63 | | 63 | X16 |
| 64 | | 64 | X15 |
| 65 | | 65 | X14 |
| 66 | | 66 | X13 |
| 67 | | 67 | X12 |
| 68 | | 68 | X11 |
| 69 | | 69 | X10 |
| 70 | | 70 | X09 |
| 71 | | 71 | X08 |
| 72 | | 72 | X07 |
| 73 | | 73 | X06 |
| 74 | | 74 | X05 |
| 75 | | 75 | X04 |
| 76 | | 76 | X03 |
| 77 | | 77 | X02 |
| 78 | | 78 | X01 |
| 79 | | 79 | X00 |
| 80 | | 80 | Dummy |

| REMARKS | |
|-----------------------|--------------|
| FPC PATTERN PITCH | 0.5mm |
| FPC PATTERN WIDTH | Cu 0.2-0.3mm |
| | Ag 0.1mm |
| CIRCUIT PATTERN WIDTH | 0.1mm |
| ○ TOLERANCE | ±0.3mm |

| ITEM | MATERIAL | REMARKS |
|------|--------------------|------------------|
| 1 | TOP ITO FILM | t=0.1mm |
| 2 | BOTTOM ITO FILM | t=0.1mm |
| 3 | FPC | POLYIMIDE 12.5μm |
| 4 | REINFORCEMENT FILM | POLYIMIDE 22μm |
| 5 | STIFFENER | POLYIMIDE 22μm |
| 6 | ADHESIVE SHEET | OCA 50μm |
| 7 | ADHESIVE SHEET A | OCA 100μm |
| 8 | SEPARATE FILM | |
| 9 | SEPARATE FILM | |

TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

| | |
|----------------------|---------------|
| PART No. | DATE |
| DUS-XF185WA060A | Jan/29/2021 |
| TYPE | DMC Co., Ltd. |
| Projected Capacitive | |
| DIMENSIONAL DRAWING | |

