


CN-1 PinOut	CN-2 PinOut
1	Quantity
2	Quantity
3	Quantity
4	Quantity
5	Quantity
6	Quantity
7	Quantity
8	Quantity
9	Quantity
10	Quantity
11	Quantity
12	Quantity
13	Quantity
14	Quantity
15	Quantity
16	Quantity
17	Quantity
18	Quantity
19	Quantity
20	Quantity
21	Quantity
22	Quantity
23	Quantity
24	Quantity
25	Quantity
26	Quantity
27	Quantity
28	Quantity
29	Quantity
30	Quantity
31	Quantity
32	Quantity
33	Quantity
34	Quantity
35	Quantity
36	Quantity
37	Quantity
38	Quantity
39	Quantity
40	Quantity
41	Quantity
42	Quantity
43	Quantity
44	Quantity
45	Quantity
46	Quantity
47	Quantity
48	Quantity
49	Quantity
50	Quantity
51	Quantity
52	Quantity
53	Quantity
54	Quantity
55	Quantity



REMARKS		
FPC PATTERN PITCH		0.5mm
FPC PATTERN WIDTH	Cu	0.2-0.3mm
	-	mm
CIRCUIT PATTERN WIDTH	Ag	0.1mm
	-	mm
○ TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1	TOP ITO GLASS	t=1.1mm
2	BOTTOM ITO GLASS	t=1.1mm
3	FPC	POLYIMIDE 12.5μm Electrolytic copper foil GOLD
4	REINFORCEMENT FILM	POLYIMIDE 25μm
5	STIFFENER	POLYIMIDE 225μm
6	ADHESIVE SHEET	150μm
7	PROTECTION TAPE	POLYESTER 25μm

Edges and corners of ITO glass may be chamfered without affecting product specification.

PART No.	DATE	SCALE
DUS-156WD060C	Oct/14/25	NTS
TYPE		UNIT
STANDARD TOUCHSCREEN		mm
DIMENSIONAL DRAWING	DMC Co., Ltd.	